

## PATENT COOPERATION TREATY

## PCT

REC'D 13 JUL 2005

WIPO

PCT

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference 71962PC/JM	FOR FURTHER ACTION See Form PCT/IPEA/416	
International application No. PCT/SE2004/000255	International filing date (day/month/year) 31.03.2003	Priority date (day/month/year) 25.02.2004
International Patent Classification (IPC) or national classification and IPC B66C 1/12, F16G 15/00		
Applicant Frenolink Förvaltnings AB et al		

- This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.
- This REPORT consists of a total of 3 sheets, including this cover sheet.
- This report is also accompanied by ANNEXES, comprising:
  - ☒ (sent to the applicant and to the International Bureau) a total of 8 sheets, as follows:
    - ☒ sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).
    - ☐ sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.
  - ☐ (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)) \_\_\_\_\_, containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).

- This report contains indications relating to the following items:
 

<input checked="" type="checkbox"/>	Box No. I	Basis of the report
<input type="checkbox"/>	Box No. II	Priority
<input type="checkbox"/>	Box No. III	Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
<input type="checkbox"/>	Box No. IV	Lack of unity of invention
<input checked="" type="checkbox"/>	Box No. V	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
<input type="checkbox"/>	Box No. VI	Certain documents cited
<input type="checkbox"/>	Box No. VII	Certain defects in the international application
<input type="checkbox"/>	Box No. VIII	Certain observations on the international application

Date of submission of the demand  03.09.2004	Date of completion of this report  28.06.2005
Name and mailing address of the IPEA/SE Patent- och registreringsverket Box 5055 S-102 42 STOCKHOLM Facsimile No. +46 8 667 72 88	Authorized officer  Lena Nilsson / JA A Telephone No. +46 8 782 25 00

# INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2004/000255

## Box No. I Basis of the report

1. With regard to the language, this report is based on the international application in the language in which it was filed, unless otherwise indicated under this item.

- ☐ This report is based on a translation from the original language into the following language \_\_\_\_\_, which is the language of a translation furnished for the purposes of:
- ☐ international search (under Rules 12.3 and 23.1(b))
  - ☐ publication of the international application (under Rule 12.4)
  - ☐ international preliminary examination (under Rules 55.2 and/or 55.3)

2. With regard to the elements of the international application, this report is based on *(replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):*

- ☐ the international application as originally filed/furnished
- ☒ the description:
- pages 1-10 as originally filed/furnished
- pages\* 11-13 received by this Authority on 22.06.2005
- pages\* \_\_\_\_\_ received by this Authority on \_\_\_\_\_
- ☒ the claims:
- pages \_\_\_\_\_ as originally filed/furnished
- pages\* \_\_\_\_\_ as amended (together with any statement) under Article 19
- pages\* 14-17 received by this Authority on 22.06.2005
- pages\* \_\_\_\_\_ received by this Authority on \_\_\_\_\_
- ☒ the drawings:
- pages 1-2, 4-9 as originally filed/furnished
- pages\* 3 received by this Authority on 16.02.2005
- pages\* \_\_\_\_\_ received by this Authority on \_\_\_\_\_
- ☐ a sequence listing and/or any related table(s) – see Supplemental Box Relating to Sequence Listing.

3. ☐ The amendments have resulted in the cancellation of:

- ☐ the description, pages \_\_\_\_\_
- ☐ the claims, Nos. \_\_\_\_\_
- ☐ the drawings, sheets/figs \_\_\_\_\_
- ☐ the sequence listing (*specify*): \_\_\_\_\_
- ☐ any table(s) related to the sequence listing (*specify*): \_\_\_\_\_

4. ☐ This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).

- ☐ the description, pages \_\_\_\_\_
- ☐ the claims, Nos. \_\_\_\_\_
- ☐ the drawings, sheets/figs \_\_\_\_\_
- ☐ the sequence listing (*specify*): \_\_\_\_\_
- ☐ any table(s) related to the sequence listing (*specify*): \_\_\_\_\_

\* If item 4 applies, some or all of those sheets may be marked "superseded."

## INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2004/000255

**Box No. V** Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

## 1. Statement

Novelty (N)	Claims	<u>1-10</u>	YES
	Claims		NO
Inventive step (IS)	Claims	<u>1-10</u>	YES
	Claims		NO
Industrial applicability (IA)	Claims	<u>1-10</u>	YES
	Claims		NO

## 2. Citations and explanations (Rule 70.7)

## Documents cited in the International Search Report:

D1: US, A, 5732545  
D2: DE, A1, 4239482  
D3: DE, A1, 3922304  
D4: GB, A, 2127129  
D5: WO, A1, 0221014

Due to reconsideration of the cited documents D1 and D2 in the international search report of 28.06.2004, these documents are now regarded as A-documents.

The cited documents represent the general state of the art. The invention defined in claims 1-10 is not disclosed by any of these documents.

The cited prior art does not give any indication that would lead a person skilled in the art to the claimed chain shortening device. Therefore, the claimed invention is not obvious to a person skilled in the art.

Accordingly, the invention defined in claims 1-10 is novel and is considered to involve an inventive step. The invention is industrially applicable.

$$L = n \times p + q$$

where

n is an odd integer  $> 0$

p is the inner length of each chain link,

5  $0 < q < 3.5d$ , and

d is the material thickness of each chain link.

Preferably, the distance  $q = 2.2d$  as shown in figs. 1A and 1B. However, the distance q could be slightly longer, up to  $3d$ , or  
10 shorter than shown down to  $2d$ . With such dimensional limits of the shortening device, it is possible to let the chain links take the full load without transferring any part of the load to the shortening device when the chain is arranged as a straight chain portion along the longitudinal axis D while  
15 still being coupled to the shortening device (as shown in figs. 1A, 1B and 3E. Furthermore, the limit  $q = 2d$  is a necessity for  $n = 1$ . Hereby, it is possible to use the chain to its full strength (although only at full length) without having to detach the shortening device from the chain.

20

Figs. 4A and 4B illustrate how the chain shortening device 10 can be used when lifting a box-like object O by means of four chain portions C1, C2, C3 and C4 connected at the top to a master link 50 and at the bottom to four corners of the object  
25 O. Two of the chain portions, C1 and C2, are provided with chain shortening devices. By adjusting the effective lengths of these chain portions, it is possible to balance the orientation of the object, even if the corner points are located differently for different objects, as illustrated in  
30 figs. 4A and 4B. In case, there are only two or three chain

portions connected to a master link 50, it is generally sufficient to adjust the length of only one chain portion, in particular by means of the attachable and detachable chain shortening device according to the invention. It is possible to attach one or more chain shortening devices without detaching the chain portions from the master link or from the load.

A second embodiment of the chain shortening device is shown in figs. 2A and 2B. The elongated body 10' is shorter and has no retainer members. Its length between the opposite seating surfaces A and B is slightly longer to one link ( $n = 1$  in the above formula). Also, the central lead-through opening 20E' is somewhat shorter as compared to figs. 1A and 1B. Otherwise, this embodiment is substantially like the first embodiment.

Of course, it is also possible to have a longer body 10 than the first embodiment of figs. 1A and 1B. This first embodiment is very advantageous in terms of strength, relative low weight and easy manual handling. In this respect, it should be noted that the overall weight and strength is improved by the diverging free end portions as compared to an embodiment as disclosed in the above-mentioned German patent specification (with mutually parallel free end portions of the body).

A third embodiment of the chain shortening device is shown in figs. 9A and 9B. Here, the elongated lead-through opening 20'''E is provided with a waist portion 22 located in the mid portion of the elongated body 10'''. The waist portion 22 has a reduced width  $w'''$  which is smaller than the outer width  $w$  of the associated chain links. In this way, two apertures 20'''F and 20'''G are formed on each side of the waist portion 22, these two apertures 20'''F, 20'''G communicating with each

other. Such an embodiment works very well. An end link L0 of a loop 41 of a chain can be threaded through the opening 20'''E in upright position. Thereupon, the parallel strands 42,43 of the loop 41 can be pulled through the respective apertures  
5 20'''F, 20'''G. Because of the shape of the opening 20'''E, the two strands 42,43 are guided smoothly in the respective aperture 20'''F, 20'''G and prevents the strands from being twisted.

CLAIMS

1. A chain shortening device for shortening an associated chain consisting of oblong links having a material thickness d, an outer width w and an outer length l which is longer than said outer width w, said chain shortening device comprising:
- a unitary elongated body (10) shaped generally like the letter "C" with first and second slot portions (20C,20D) located at the free end portions of the "C",
  - each of said slot portions including a first and a second pocket-like configuration (20A,20B), respectively, for positioning selected links (L2,L6) of said associated chain in a first and a second coupling position, respectively, and
  - each of said first and second slot portions having, adjacent to said pocket-like configuration, a width which is wider than the material thickness d of said chain links but narrower than the outer width w of said chain links, and adjacent to a mid portion of said elongated body, a widened slot portion defining an aperture, which is wide enough to permit threading said associated chain through said aperture,
  - so that, upon coupling said associated chain to the shortening device with two selected links located in said first and second coupling positions, respectively, the chain links located between the two selected links will form either a straight chain portion, extending at the side of said mid portion of the elongated, generally C-shaped body, or a longer slack chain portion enabling the effective shortening of said associated chain,
- characterised** in that
- said slot portions form parts of a central, single slot (20) extending continuously and longitudinally between said first and second pocket-like configurations (20A,20B), and
  - said central, single slot has a widened mid portion

forming a central lead-through opening (20E), which includes said two apertures and which is dimensioned to permit threading through a loop (41) of said associated chain with two parallel strands (42,43),

- 5 - whereby the shortening device can be handled as a separate unit and be attached sideways to an existing, associated chain for the purpose of shortening the effective length thereof.

2. A chain shortening device as defined in claim 1, wherein  
10 said central lead-through opening (20E) is elongated in the longitudinal direction (D) of said elongated body (10).

3. A chain shortening device as defined in claim 2, wherein  
15 the width of the slot portions (20C,20D) adjacent to the central lead-through opening (20E) is only slightly wider than said material thickness d of the links of the associated chain, so as to prevent coupling of the shortening device to a chain consisting of links being stronger than those of the associated chain, and the length of central lead-through  
20 opening (20E) is such as to permit threading through a loop (41) of an associated chain with the links of the two parallel strands (42,43) of the loop being positioned next to each other in the longitudinal direction (D) of the elongated body (10).

25

4. A chain shortening device as defined in claim 3, wherein said central lead-through opening (20E) is wider than said outer width w of the links of said associated chain and longer than 1.5 times that width w.

30

5. A chain shortening device as defined in claim 1, wherein said central lead-through opening has, at said mid portion of said elongated body (10), a waist portion with a reduced



width, which is less than the outer width  $w$  of said chain links but greater than the material thickness  $d$  of said chain links, said waist defining said two apertures on opposite sides thereof so as to permit threading through a central portion of an upright link forming the leading end of said loop (41) of said chain through said waist portion and threading through the adjoining parallel strands (42,43) through said two apertures.

6. A chain shortening device as defined in claim 5, wherein each of said apertures are wider than said outer width  $w$  of said chain links but shorter, in the longitudinal direction of said elongated body (19), than said outer width  $w$ .

7. A chain shortening device as defined in any one of the preceding claims, wherein retainer members (30A,30B) are located in each of said first and second slot portions (20C,20D) so as to selectively retain said first and second selected links (L2,L6) adjacent to said first and second coupling positions.

8. A chain shortening device as defined in any one of the preceding claims, wherein said free end portions of said elongated body (10) are directed obliquely away from each other.

9. A chain shortening device as defined in any one of the preceding claims, wherein seating surfaces (A and B), which form parts of said pocket-like configurations and face towards each other, are located at a mutual distance  $L$  from each other, said distance  $L$  being

$$L = n \times p + q$$

where

n is an odd integer  $> 0$

p is the inner length of each chain link of the  
associated chain,

5  $0 < q < 3.5 d$

d is the material thickness of each chain link.

10. A chain shortening device as defined in claim 10, wherein  
 $2d < q < 3d$ .




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 3D




Fig. 3E




Fig. 3F